

## **OmegaPearla (series 6400)**

*Classy Low Sheen Pearl Finish, Water-base Decorative Paint*

<b>CHARACTERISTICS</b>	OmegaPearla is water based acrylic copolymers paint that allows obtaining exquisite and luxurious, it is an elegant finish with a subtle sparkle or shimmer, creating visual texture and directional effect. With a low sheen, the intriguing surface is full of movement and tonal interest. The finish depend on the hand of the applicator, creating a unique and visually striking wall coating at close quarters, yet subtle when viewed from a distance.		
<b>SURFACE PREPARATION</b>	All surfaces to be painted should be clean, dry and free from loose, before applying OmegaPearla, one or two base coat of primer should be applied (usually OmegaLux series 500) taking into consideration, the primer color should be within the same tone of the final desired finish.		
<b>APPLICATION</b>	<p>Stir smoothly before use; Apply two coats of OmegaPearla as a base, leaving two hours in between coats at a constant temperature of 25°C, using a short wool roller. During the final stage of base coat application, apply OmegaPearla in one direction only, i.e. without changing the direction of the roller-strokes.</p> <p>After apply a third and final layer of OmegaPearla that is approximately 1.5 to 2 mm thick in the same colour as the base coats using a short wool roller, while the product is still wet, touch up the paint using a stainless steel trowel, make cross-shaped strokes with the trowel in all directions (watch Omega tutorial CD). The final stage can be applied in many different techniques using various tools, to create unique patterns and reflects.</p>		
<b>THINNING</b>	Ready to use, but in some special cases you may add 5% clean water.		
<b>COVERAGE</b>	Depending on the porosity of the area to be painted, approx. 3 to 4 meter square per liter.		
<b>DRYING TIME</b>	Dry to touch (Dust Free)	3 - 4	Hours.
	Dry to re-coat	6 - 8	Hours.
	Dry to handle	12 - 24	Hours.