

OmegaExPutty No. 101

Ready mixed putty filler, for exterior fair faced concrete

Hide small defects – Multi surface

OmegaExPutty is fine graded filler and surfacing material to be used over almost any exterior surface to fill cracks, holes and undulations to improve the surface for final paint. It can be used on all types of exterior & interior building surfaces plaster, concrete, building boards.

OmegaExPutty is supplied ready mixed with no mixing or adding of water required. OmegaBrutePutty is water-based, non-toxic and contains no asbestos fibers or other harmful ingredients.

Application: Make a first filling of any larger damages and holes using ready mixed concrete cement plaster and use OmegaBrutePutty to fill all small & intermediatesize holes. When used on old painted surfaces ensure that the adhesion of the old paint is good.

TECHNICAL DATA

Article no.	OmegaExPutty - 101
Colour	Concrete tone
Thickness per coat	>2mm
Packaging	25-kg plastic pail
Density	1,75 kg per liter
Solid content, by weight	80% nominal
Solid Content, by volume	69% nominal
Drying time	12 hours per mm with temp+15 rh 75-85%
Coverage	1 liter per square meter and mm thickness
Application	by hand
Clean / thin	With water
Flash point – fire rating	None – class 0 surface spread of flame
Storage	Frost free and dry- 1 year in unopened container
Toxicity	Free from toxic matter
General	Water borne dispersion filler base on calcium carbonate and natural sand with preservatives and rust inhibitors added