

## **OmegaUniversalPutty No.110**

*Ready mixed putty filler, Multi-purpose uses*

*Hide surface defects with good finishing properties*

Ready to use filler to fill in small gaps and small cracks and where thicker layers is required, its used over almost any internal surface to fill cracks, holes as first coat over fair-faced block-work, shuttered concrete etc., also suitable for application to aerated concrete blocks and panels.

OmegaMultiPurposePutty is supplied ready mixed with no mixing or adding of water required, OmegaMultiPurposePutty is water-base, non-toxic and contains no asbestos fibers or other harmful ingredients.

Application is done by spray using a mono-pump type spray machine or by hand. Apply in one or several coats, with intermittent drying. Make a first filling of any larger damage and undulations.

### **TECHNICAL DATA**

Article no.	OmegaUniversalPutty - 110
Color	White
Thickness per coat	2 to 6 mm
Packaging	25-kg plastic pail
Density	1.70 kg per liter
Solid content, by weight	78% nominal
Solid content, by volume	60% nominal
Drying time	12 hours per mm with temp+15 rh 75-85%
Coverage	1 liter per square meter and mm thickness
Application	By spray or by hand
Clean / thin	With water
Flash point – fire rating	None – class 0 surface spread of flame
Storage	Frost free and dry- 1 year in unopened container
Toxicity	Free from toxic matter
General	Water borne dispersion filler base on calcium carbonate and natural sand with preservatives and rust inhibitors added