

OmegaVarnish (series 150)

Urethane alkyd base, transparent, hard, protective finish

Available in high gloss and flat finish

CHARACTERISTICS OmegaVarnish is based on special alkyd oil suitable for interior and exterior wooden surfaces. It is hard wearing and protects against knocks and spills, and gives an exclusive durable finish.

It is recommended for interior and exterior on all kinds of untreated hardwood, softwood, plywood, chip board, etc. Can also be used on wood previously treated with other wood protections.

SURFACE PREPARATION

Substrates must be clean and dry. Surface contamination is to be removed by thoroughly rubbed down in the direction of the wood grain, using a suitable abrasive paper and dusted off.

APPLICATION

Could be done by brush, roller and airless spray.

THINNING

Use mineral spirit up to 20% for brush or roller application and up to 30% for airless spray application.

COVERAGE

Depending on the porosity of the area to be treated, approx. 12sq m. per liter.

STORAGE

Flashpoint is 38°C. Solvent based, store away from direct sunlight, naked flames, sparks and other heat sources.

HEALTH AND SAFETY PRECAUTIONS:

Must not be used where ventilation is poor. Gloved and goggles are recommended when applying by brush or spray. Flammable- Keep away from sources of ignition. Harmful if taken internally

DRYING TIME

Dry to touch (Dust Free)	3 – 4	Hours.
Dry to re-coat	6 – 8	Hours.
Dry to handle	24	Hours.