

- DESCRIPTION:** OmegaCrete is a one coat, tough, high solids, and pure acrylic concrete sealer in a solvent base. It is designed to protect and beautify all types of cured concrete with a high gloss, durable clear coating. This sealer is non-yellowing to preserve the appearance of all types of decorative concrete. OmegaCrete protects and beautifies surfaces such as colored, stamped, and exposed aggregate. It also protects concrete pavers and acid-stained surfaces. Paver joints will be stabilized, and concrete pavers will be sealed.
- PREPARATION:** Clean dirt, wax, grease, oil and other contaminants from the surface. Be sure to remove any foreign coating unless previous coating is same or similar solvent-based sealer. Make sure the surface is clean, dry and sound. Clean oily concrete with SOL-180. Use a bristle brush for heavily oiled spots. Rinse well with a pressure washer. Allow 24 hours to dry. Concrete must be porous enough to accept water. Dense concrete surfaces may require mechanical preparation to accept sealer. Apply only when surface and air temperatures are above 10° C and below 35° C. Do not apply to excessively hot surfaces as rapid drying may cause bubbles or streaking to form. For pavers, sweep away any loose sand.
- APPLICATION:** For exterior application, only. Perform test to ensure compatibility. Brush may be used where roller won't reach. Do not pour directly from can to concrete. Apply evenly from can or other metal container with solvent resistant roller. Use a long nap roller for exposed aggregate, a medium nap roller for textured surfaces and a short nap roller for smooth surfaces. Keep roller soaked. Wait until the surface is tack-free before applying a second coat by cross-rolling perpendicular to the first coat. Do not thin product. Foot traffic should be avoided for 4 hours. Vehicle traffic should be avoided for 48 hours. Do not apply if rain is imminent. Cooler temperatures or increased humidity will slow the drying time.
- SOLVENT:** Omega SOL-180
- PACKAGING:**
- Pail 15 liter
 - Gallon 3 liter
- COVERAGE:** Two thin coats are recommended yielding the following net coverage.
- Smooth Troweled (etch required): 75 m² per pail
 - Textured or Stamped: 60 m² per pail
- CLEANUP:** Clean up tools with Xylene, Toluene or Lacquer Thinner. Do not use Paint Thinner, Mineral Spirits or water.
- MAINTENANCE:** Clean sealed surface with water only. Reseal surface as needed, but no more often than every two years to prevent buildup of sealer.

WARNING

COMBUSTIBLE. EYE, SKIN & RESPIRATORY IRRITANT. Contains Aromatic Naptha. Do not use near heat, sparks or open flames. Avoid contact with eyes and prolonged contact with skin. Use only with adequate ventilation. Do not inhale vapors. Do not ingest. See Safety Data Sheet for more info.

FIRST AID

In case of eye contact, flush with water for 15 minutes. In case of skin contact, wash thoroughly with soap and water. If swallowed, do not induce vomiting. Immediately contact hospital ER or physician. If vapors are inhaled or breathing becomes difficult, move person to fresh air. Seek medical attention if skin, eye or respiratory irritation persist. See Safety Data Sheet for more info.