

DESCRIPTION OmegaRoll is a ready-mixed, highly decorative, impermeable, durable rendering for interiors and exteriors based on Acrylic Copolymer resins. It provides non-cracking impermeable wall coating. It's come with a 10-year guarantee against fading and peeling; OmegaRoll is the ideal economical substitute for natural stone facades.

PRINCIPAL CHARACTERISTICS

- Especially designed for use on all types of external and internal surfaces (masonry of cement plaster, wood...etc.).
- Hides surface defects.
- Tough, durable coating.
- Excellent adhesion to wall surfaces.
- Easy and fast application.
- Highly resistant to chemical and saline air and to the ultra violet rays of the sun.
- Easy and good wash-ability.
- This product can be diluted with small percent of water.

TECHNICAL DATA

Binders	Acrylic Copolymer
Fillers	Crushed and precisely graded fillers
Pigments	Lime and light fast
Additives	Fungicides, plasticity and anti-corrosion agents
Color	Please refer to OmegaRoll Textured color guide
Dilution	With 5% pure water if required
Drying Time	3 – 4 hours in normal conditions
Coverage	25kg covers 20 m ² for 2mm thickness; it may varies upon texture request
Specific Gravity	1.70
Adhesion	To concrete: 0.4 MPA
Toxicity	Non-toxic
Fire Resistance	Do not sustain fire. Flames spread class 0 ASTM E84-81A
Storage	12 months in clean dry conditions in unopened containers

SURFACE PREPARATION

- Surface should be free from dust, dirt and foreign matter
- Surface defects can be repaired with ACRYLIC FILLER.
- Before applying OmegaRoll old surface, all defective paintwork should be removed and the surface should be washed with a soda solution. Porous and dusting surfaces should receive coat of penetrating primer such as OmegaPrimer no. 1000.

APPLICATION Use good quality Roller

PACKING In 17 liters cylindrical pail

DRYING TIME

Dry to touch (Dust Free)	30 – 60	Minutes.
Dry to re-coat	4 - 6	Hours.
Dry to handle	24	Hours.