

## OmegaSilk (series 500)

High Quality Emulsion Paint / Silky Finish  
Acrylic Base

**CHARACTERISTICS:** gives Silky finish, which would be used on all exterior and interior concrete walls, ceiling and putty filler to provide top smooth finish with outstanding durability. The high technological level of this product provides an easy application, fast drying, higher opacity, excellent coverage, leveling and adherence to the surface. Providing waterproofing effect to the surfaces, keeping it beautiful for much longer protected from mould and alkalinity.

**SURFACE PREPARATION:** Substrate must be clean and free of chalk, grease, silicone, wax, mildew, and loose or peeling paint. Glossy surfaces must be dulled. Mildew and fungus may be removed by treating the affected area with a 50/50 solution of chlorine bleach and water. Allow mixture to soak in (15 to 20 min.) then pressure clean thoroughly to remove contamination. Chalky walls must be pressure cleaned to eliminate chalking condition.

**APPLICATION:** Paint should be stirred thoroughly to a smooth consistency immediately before use. Prior to painting, ensure having enough paint boxed or mixed in one container to complete an entire section. This practice is especially important with custom mixed colors. Product may be brush, roller, or spray applied. Thin, only with small amounts of clean water. Do not apply when air or surface temperature below 5°C or if rain is imminent. Add no modifiers. Paint will dry to touch in 30 minutes and will be ready to accept recoat in 4 hours.

**THINNING:** With clean water 15 – 25 % in some special cases thin up to 25 – 35 % when applying the first coat directly to unprimed absorbent surfaces or in hot climates.

**COVERAGE:** Each U.S. gallon should cover an area between 50 – 70 m<sup>2</sup> depending on the texture absorption and color of the surface.

**CLEAN UP:** Hands and tools may be cleaned with soapy water and rinsed with clean water. Spray equipment should be given a final treatment of Mineral Spirits to prevent rusting.

<b>DRYING TIME:</b>	DRY TO TOUCH (DUST FREE)	30 – 60	MINUTES.
	Dry to re-coat	4 - 6	Hours.
	Dry to handle	24	Hours.

**CAUTION:** Keep from freezing. Avoid prolonged contact with skin or breathing spray mist. Do not take internally. Close container after each use. Use with adequate ventilation. **IMPORTANT:** Spray equipment must be operated in strict accordance with manufacturer's instructions. When spray applying, wear spray mask, eye protection and protective clothing. **FIRST AID:** In case of skin contact, wipe area clean with cloth and wash thoroughly with soap and water; for eyes, flush with water for 15 minutes and get medical attention. If swallowed, get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN.**