

## OmegaEnamel (series 900)

High quality alkyd solvent base enamel paint (Interior / Exterior)

Available in High Gloss, Semi-Gloss and Flat finish

**CHARACTERISTICS:** A specially formulated high quality Alkyd Enamel synthetic paint, it has a good opacity with excellent leveling properties without leaving brush marks, non-toxic, extreme wash-ability, free from disagreeable odor after drying, and resistant to mineral and vegetable oils, aliphatic hydrocarbons, splashes of benzene and alcohol.

**RECOMMENDED USES:** For exterior and interior new or repaint works of wood, metal, masonry surfaces such as windows, doors, cabinets, kitchens, bathrooms and fair-faced concrete...etc.

**SURFACE PREPARATION:** Surfaces must be solid dry and free of dirt, grease, oils, salt, and other contaminants. Previously painted surfaces that are checked marred or glossy should be roughened with sandpaper to insure good inter-coat adhesion. Steel surfaces should be cleaned properly of rust or loose particles.

**COVERAGE:** In normal application 50 – 60 meter square per U.S. Gallon for one coat, it may reach up to 80 meter square depending on texture absorption, and color of the surface.

**APPLICATION:** Could be done by brush, roller and airless spray.

**THINNING:** Use mineral spirit up to 20 % for brush or roller application and up to 30 % for airless spray application.

### TECHNICAL DATA

Density	1.06 kg per liter
Solid content, by weight	50-55% nominal
Solid content, by volume	45-50% nominal
Thinning & Cleaning	White Spirit
Flash point	>39 ° C
Storage	Frost free and dry- 1 year in unopened container

<b>DRYING TIME</b>	Dry to touch (Dust Free)	4 - 6	Hours.
	Dry to re-coat	16	Hours.
	Dry to handle	48	Hours.